



呼び径170<sup>m</sup>/m以上

単位：mm

呼び径		止 め 輪 寸 法						
		$d_3$		$t$		$b$	$a$	$d_0$
		寸法	公差	寸法	公差	約	約	最小
R-	42	45.5	$\pm 0.4$	1.75	$\pm 0.07$	4.0	5.8	2.5
	45	48.5				4.5	5.9	
	47	50.5				4.5	6.1	
	48	51.5				4.5	6.2	
	52	56.2	5.1	6.5				
	55	59.2	5.1	6.5				
	56	60.2	5.1	6.6				
	58	62.2	5.1	6.8				
	60	64.2	5.5	6.8				
	62	66.2	5.5	6.9				
	63	67.2	5.5	6.9	3.0			
	65	69.2	5.5	7.0				
	68	72.5	6.0	7.4				
	70	74.5	6.0	7.4				
	72	76.5	6.6	7.4				
	75	79.5	6.6	7.8				
	78	82.5	6.6	8.0				
	80	85.5	7.0	8.0				
	82	87.5	7.0	8.0				
	85	90.5	7.0	8.0				
88	93.5	7.6	8.2	$\pm 0.09$				
90	95.5	7.6	8.3					
92	97.5	8.0	8.3					
95	100.5	8.0	8.5					
98	103.5	8.3	8.7					
100	105.5	8.3	8.8					

# 穴用C型止め輪(スナップリング)【JIS B 2804】

単位：mm

呼び径		止 め 輪 寸 法						
		d <sub>3</sub>		t		b	a	d <sub>0</sub>
		寸法	公差	寸法	公差	約	約	最小
R-	102	108.0	±0.55	4.0	±0.09	8.9	9.0	4.0
	105	112.0				8.9	9.1	
	108	115.0				8.9	9.5	
	110	117.0				8.9	10.2	
	112	119.0				8.9	10.2	
	115	122.0	±0.65			9.5	10.2	
	120	127.0				9.5	10.7	
	125	132.0				10.0	10.7	
	130	137.0				10.0	10.7	
	135	142.0				10.8	11.0	
	140	147.0	+1.26 -0.63			10.8	11.0	
	145	152.0				10.8	11.0	
	150	158.0				11.5	11.8	
	155	164.0				11.5	11.8	
	160	169.0				12.0	12.5	
	165	174.5		12.0	12.7			
	170	179.5		12.0				
	175	184.5		12.3				
	180	189.5		13.0				
	185	194.5		13.5				
	190	199.5	+1.44 -0.72	13.5				
	195	204.5		13.5				
	200	209.5		14.0				
	205	217.0		14.0				
	210	222.0		14.0				
	215	227.0		14.0				
	220	232.0		14.0				
	225	237.0		14.0				
	230	242.0		14.0				
	235	247.0		14.0				
240	252.0	+1.62 -0.82	5.0	±0.15	14.0			
245	257.0				14.0			
250	262.0				14.0			
260	275.0				16.0			
270	285.0				16.0			
280	295.0				16.0			
290	305.0				16.0			
300	315.0				16.0			