



呼び径170<sup>m</sup>/m以上

単位：mm

| 呼び径 |       | 止め輪寸法          |       |       |       |      |       |                |     |     |
|-----|-------|----------------|-------|-------|-------|------|-------|----------------|-----|-----|
|     |       | d <sub>3</sub> |       | t     |       | b    | a     | d <sub>0</sub> |     |     |
|     |       | 寸法             | 公差    | 寸法    | 公差    | 約    | 約     | 最小             |     |     |
| S-  | 50    | 45.8           | ±0.40 | 2.0   | ±0.07 | 5.0  | 6.7   | 2.5            |     |     |
|     | 55    | 50.8           | ±0.45 |       |       | 2.5  | ±0.08 |                | 5.0 | 7.0 |
|     | 60    | 55.8           |       |       |       |      |       |                | 5.5 | 7.2 |
|     | 65    | 60.8           |       | 6.4   | 7.4   |      |       |                |     |     |
|     | 68    | 63.5           |       | 6.4   | 7.8   |      |       |                |     |     |
|     | 70    | 65.5           |       | 6.4   | 7.8   |      |       |                |     |     |
|     | 72    | 67.5           |       | 7.0   | 7.9   |      |       |                |     |     |
|     | 75    | 70.5           |       | 7.0   | 7.9   |      |       |                |     |     |
|     | 78    | 73.5           | 7.4   | 8.1   |       |      |       |                |     |     |
|     | 80    | 74.5           | 7.4   | 8.2   |       |      |       |                |     |     |
|     | 82    | 76.5           | 7.4   | 8.3   | 3.0   |      |       |                |     |     |
|     | 85    | 79.5           | 3.0   | ±0.09 |       | 8.0  | 8.4   |                |     |     |
|     | 88    | 82.5           |       |       |       | 8.0  | 8.6   |                |     |     |
|     | 90    | 84.5           |       |       |       | 8.0  | 8.7   |                |     |     |
|     | 95    | 89.5           |       |       | 8.6   | 9.1  |       |                |     |     |
|     | 100   | 94.5           | ±0.55 | 4.0   | 9.0   | 9.5  | 4.0   |                |     |     |
|     | 105   | 98.0           |       |       | 9.5   | 9.8  |       |                |     |     |
|     | 110   | 103.0          |       |       | 9.5   | 10.0 |       |                |     |     |
|     | 115   | 108.0          |       |       | 9.5   | 10.5 |       |                |     |     |
|     | 120   | 113.0          |       |       | 10.3  | 10.9 |       |                |     |     |
|     | 125   | 118.0          |       |       | 10.3  | 11.3 |       |                |     |     |
| 130 | 123.0 | 11.0           |       |       | 11.5  |      |       |                |     |     |
| 135 | 128.0 | +0.63<br>-1.26 | 4.0   | 11.0  | 11.5  |      |       |                |     |     |
| 140 | 133.0 |                |       | 11.0  | 11.8  |      |       |                |     |     |
| 145 | 138.0 |                |       | 11.6  | 11.8  |      |       |                |     |     |
| 150 | 142.0 |                |       | 11.6  | 12.3  |      |       |                |     |     |
| 155 | 146.0 |                |       | 12.2  | 12.7  |      |       |                |     |     |
| 160 | 151.0 |                |       | 12.2  | 12.9  |      |       |                |     |     |
| 165 | 155.5 |                |       | 12.9  | 13.1  |      |       |                |     |     |
| 170 | 160.5 | 12.9           |       |       |       |      |       |                |     |     |

# 軸用C型止め輪(スナップリング)【JIS B 2804】

単位：mm

| 呼び径 |       | 止 め 輪 寸 法      |                |       |                |      |   |                |
|-----|-------|----------------|----------------|-------|----------------|------|---|----------------|
|     |       | d <sub>3</sub> |                | t     |                | b    | a | d <sub>0</sub> |
|     |       | 寸法             | 公差             | 寸法    | 公差             | 約    | 約 | 最小             |
| S-  | 175   | 165.5          | +0.63          | 4.0   | ±0.09          | 12.9 |   | 4.0            |
|     | 180   | 170.5          | -1.26          |       |                | 13.5 |   |                |
|     | 185   | 175.5          | +0.72<br>-1.44 |       |                | 13.5 |   |                |
|     | 190   | 180.5          |                |       |                | 14.0 |   |                |
|     | 195   | 185.5          |                |       |                | 14.0 |   |                |
|     | 200   | 190.5          |                |       |                | 14.0 |   |                |
|     | 205   | 193.0          |                |       |                | 14.0 |   |                |
|     | 210   | 198.0          |                |       |                | 14.0 |   |                |
|     | 215   | 203.0          |                |       |                | 14.0 |   |                |
|     | 220   | 208.0          |                |       |                | 14.0 |   |                |
|     | 225   | 213.0          |                | 14.0  |                |      |   |                |
|     | 230   | 218.0          |                | 14.0  |                |      |   |                |
|     | 235   | 223.0          | 5.0            | ±0.15 | 14.0           |      |   |                |
|     | 240   | 228.0          |                |       | 14.0           |      |   |                |
|     | 245   | 233.0          |                |       | 14.0           |      |   |                |
|     | 250   | 238.0          |                |       | 14.0           |      |   |                |
|     | 260   | 245.0          |                |       | 16.0           |      |   |                |
|     | 270   | 255.0          |                |       | 16.0           |      |   |                |
|     | 280   | 265.0          |                |       | 16.0           |      |   |                |
|     | 290   | 275.0          |                |       | 16.0           |      |   |                |
| 300 | 285.0 | 16.0           |                |       |                |      |   |                |
|     |       |                |                |       | +0.81<br>-1.62 |      |   |                |